

PRODUCT SPECIFICATION

CHAIN HOIST

Features & benefits

The electric chain hoist is tough and durable, designed to keep working in the most arduous applications. The perfect hoist to accompany the NIKO track system.

This Hoist is recognised and proven within the hire industry as the number one hoist, where high duty, combined with long heights of lifts are required.

The chain hoist is perfect for lifting loads from the roadside onto scaffold gantries.

The design enables easy access for installation and service.

Key features:

- 500kg or 1000kg SWL.
- Lifting speed up to 8 m/min.
- 3m to 30m Height of lift.
- Electric 110v.
- Thermal overload protection.
- Paired with NIKO track.



Optional Accessory

Lifting Chains



Stillage



Chain Hoist used with the NIKO Track system



PRODUCT SPECIFICATION

CHAIN HOIST

	Chain Hoist 500kg	Chain Hoist 1000kg
Maximum Height	up to 30m	up to 30m
Lifting Capacity - Goods Mode	500kg	1000kg
Lifting Capacity - Personnel Mode	n/a	n/a
Lifting Speed - Goods Mode	4 m/min or 8 m/min	4 m/min
Lifting Speed - Personnel Mode	n/a	n/a
Power Source	110v Electric	110v Electric
Breaker Rating	16a	32a
Power Requirements (Within 2m of the hoist base)	Dedicated 110v 16a Commando Socket or 3.3kw / 110v / 16a - Heavy-Duty Continuous Transformer. (Supplied By The Hoist People)	Dedicated 110v 32a Commando Socket or 3.3kw / 110v / 32a Heavy-Duty Continuous Transformer. (Supplied By The Hoist People)
Start up Current (Max)	24a	35a
Running Current (Max)	8a	12a
Cage Dimensions (Internal)	n/a	n/a
Approx. Ground Space Required	n/a	n/a
Approx. Minimum Access Required	n/a	n/a
Approx. Gate Opening Dimintions	n/a	n/a

Model	500KG (F Type)	500KG (J Type)	1000KG (L Type)
A, mm	413	471	471
B, mm	156	194	194
D, mm	279	241	241
F, mm	197	271	271
J, mm	100	138	138
L, mm	122	184	184
P, mm	168	198	198

